



Robertson Harness Inc.
 P.O. BOX 90086-0086
 Henderson, NV. 89009 USA
www.robertsonharness.com
 (702) 564-4286

These instructions are provided to the user by the manufacturer and should be saved for future reference.

Features

- Available in single and double pin.
- Can be used as a self-belay or with a belayer.
- Single pin can accept up to a 3/8" (15.9 mm) rope
- Double pin can accept up to a 1/2" (12.7mm) rope
- Wall thickness of .180 around clip-in hole and .090 around back-up bolt.
- Outstanding durability and structural design for 25 years.
- Side plates are .105" thick, made of 304 stainless steel for superior strength.
- Aluminum cylinder allows the spool to cool more rapidly than a stainless steel cylinder spool.
- Ability to accept two steel carabineers in the becket.
- The Robertson Belay spool #3015 is a platform highly recommended for commercial applications.

Qualifications

- Minimum 3 Sigma breaking strength of not less than 36 kN (8,093lb.)



Product- 3015

Description- tandem sheave

Third party rated tested

3-Sigma 3σ 50kN (11,387 lb.) SWL (F)⁵ @ 2277 lb.



Requirements

- Requires operator to maintain control of the tail at all times
- NFPA 1983 7.6.5.4 the pulley must be capable of sustaining a 8,093 lb. (36kN) static load or twice the maximum arrest force permitted on the system when certified.
- Inspect the belay spool after each use in accordance with Manufacturers criteria.
- A cursory inspection by a trained person is essential before each use of the belay spool.
- Robertson Harness recommends an annual examination of general condition and function be carried out and recorded by a qualified inspector.

WARNING

- Serious injury death may result from misusing or improper use of this equipment.
- This equipment has been designed and manufactured for use by experienced professionals only.
- Do not attempt to use this equipment without proper training.
- Do not alter this equipment in any way.
- Do not use this equipment for anything designed to create a free fall of more than six.

Robertson Harness Inc.

Proudly Made In The USA



Belay Spool Aluminum two pin

3015 3/8 - 1/2

Dimensions

Length: 3 76.2mm
 Height: 5 7/8 149.2mm
 Width: 2 5/8 67mm

* 1/2 rope recommended



Inspection

- Inspect spool for visible signs that show damage to the spool: Cracks on the side plates, heavy dents, or elongation of the clip in point.
- Inspect the sheaves for rust, pits, and grooving.
- Inspect the bolts assemblies for tightness.
- Inspect the spool for damage if dropped or impact loaded.
- Remove immediately and destroy if the equipment has been dropped from excessive heights.

Users and Operators need to maintain a log of identifying the history record of the equipment.

Sample Maintenance and Inspection Log

| Product Record Card | | | |
|---------------------|-----------|------------------|-----------|
| Product Type: | | | |
| ID /Serial #: | | | |
| Purchase Date: | | Date of 1st Use: | |
| Date Inspected | Pass/Fail | Comments | Signature |
| | | | |
| | | | |
| | | | |

Maintenance

- Protect and store the equipment away from extreme heat or extreme cold.
- Pulley should never be exposed to temperatures above 130° F (54° Celsius) or below -80° F. (Above 62° Celsius).
- Spool need to be clean and free from debris before storage.
- If necessary clean pulley with soap and water.
- Spool needs to be completely dried off before storage.
- Spool needs to be stored and maintained daily.
- Do not leave belay spool outside on the system to endure mother nature! The sheaves are not stainless steel.
- Repairs or modifications made by anyone other than Robertson Harness Inc. will void all warranties and liability.**