



Robertson Harness
Fort Collins, Colorado
Sales@robertsonharness.com
www.robertsonharness.com
(970) 682-4470

These instructions are provided to the user by the manufacturer and should be saved for future reference.

Requirements

- This harness was designed to connect the user to a suitable fall protection anchor to avoid or limit a fall, and may also allow for safe attachment to appropriate pulley's used in zip line and canopy tours.
- Anchorages selected for personal fall arrest systems must be capable of sustaining a 5,000 lb. (22.2 kN) static load or twice the maximum arrest force permitted on the system.
- These items are designed for a single user unless otherwise specified.
- Lanyard connections to the harness must be approved connectors to the appropriate fall arrest attachments on the harness.
- A cursory inspection by a "Qualified Person" is essential before each use of all equipment.
- Robertson Harness recommends an annual examination of general condition and function be carried out and recorded by a Third Party "Qualified Person" to ensure servability and proper use.
- Product should not exceeding 10 years from the date of first use.
See Service Life & Retirement Document for more details.
Call (970) 682-4470 or email Sales@RobertsonHarness.com

Qualifications

This product has been pull tested to 5000 lb. (22.24 kN)
Complies to PRCA/ANSI 1.0-1.3 5000 lb. (MBS) minimum breaking strength
Complies to ANSI Z359.1 required 5000lb. Breaking strength.
Tested to ASTM F-1772 12.1.2 / 12.2.2 Standard specification
for harnesses used in Rescue, Safety and Sport Activities.
For full body harnesses, sit harnesses, and chest harnesses.
Meets and exceeds CE qualifications and standards.



WARNING

- Serious injury death may result from misusing or improper use of this equipment.
- This equipment has been designed and manufactured for use by experienced professionals only.
- Do not attempt to use this equipment without proper training.
- Do not alter this equipment in any way.
- Do not use equipment on abrasive surfaces or around sharp objects.
- Do not store or use this nylon webbing near chemicals.
- Do not use this equipment for anything designed to purposely create a reoccurring free fall.
- Only connect to the manufactures designed main belay in the front of the harness or structural weight bearing Cypress Loop on rear of the harness, do not attempt to tie in anywhere else on this harness.
- Contact manufacturer before using in swing applications. Swing defined as a pendulum in motion from a fixed pivot point.
- Participant weight should not exceed 310 LBS.

Robertson Harness



Proudly Made In The USA

CRC 500 Series Full Body Harness w/ Dorsal D-Ring

SM. # CRC501 up to 30" Red
MED. # CRC500 up to 47" Blue
L/XL # CRC502 up to 56" Grey



Inspection

- Inspect harness for visible signs of wear and tear such as: Fading, cuts tearing or ripping on the abrasions.
- Look for fraying on the edges, burns or other possible damage.
- Carefully inspect the wear and any possible broken stitches in the tacked patterns.
- Remove from service and destroy if the equipment has been exposed to flame or high temperatures.
- Remove immediately and destroy if the equipment has been exposed to caustic chemicals such as: acids, alkalis, petroleum or bleach.

Users and Operators need to maintain a log of identifying the history record of the equipment.

Sample Maintenance and Inspection Log

Product Record Card			
Product Type:			
ID /Serial #:			
Purchase Date:		Date of 1st Use:	
Date Inspected	Pass/Fail	Comments	Signature

Maintenance

- Protect and store the equipment from direct sunlight or extreme heat sources. Webbing should never be exposed to temperatures above 120° F (62° Celsius) or below -80° F. (Above 48° Celsius).
- Protect the equipment from nylon damaging chemicals such as acids, alkalis, oxidizing agents, petroleum products and bleach.
- Hand wash the harness in cool water with small amounts of mild soap. Rinse thoroughly to remove all soap residue. Failure to remove all the soap will leave webbing stiff and will need to rinsed again.
- Do not wash webbing in Woolite.
- **Repairs or modifications made by anyone other than Robertson Harness Inc. will void all warranties and liability.**

Service Life

Please see the our Service Life Documentation for more detail.

Service Life is "One minute to Ten Year Service Life or condition, with a Fifteen Year Shelf Life." Terms and Conditions do apply on Shelf Life. Contact the manufacturer for details.



CRC500 Series Full Body Harness w/ Rear D-ring

CRC501 Small (red) CRC500 (blue) CRC502 Large (gray)

For your own safety, please read and understand all information included with this product. Retain the instructions for future use and reference as needed. Provide this sheet to anyone using or supervising the use of this harness.

Installation Instructions

- Loosen all buckles and expand the webbing. You will not need to totally unfasten the ends.
- Step down through the waist belt and leg loops. Pull the harness up and slip on the shoulder straps.
- Tighten waist belt until snug. Tighten leg straps until they are ½" larger than your thigh when tensed. (You should be able to slide your fingers between the leg strap and your thigh.)
- The quick-adjust buckle is laced with the web coming in the back of the buckle, around the slider, then out under the buckle again. Figure 1
- A minimum of 4 inches of web tailing must extend from the buckle once secured on waist, legs and chest adjust pieces.
- The shoulder straps can then be tightened to a snug fit.
- Adjust the chest strap height and snugness so that the shoulder straps will stay on the shoulders in a dynamic fall.
- The rear D-ring should rest between the shoulder blades under load.
- To tie-in, simply clip into the colored belay loop provided in the front of the harness. See figure 2.
- The rear colored loop is a structural loop for tying off at a work station or platform.

Do not attempt to tie-in anywhere other than the intended colored belay loop or rear tie off loop.

This product has been designed, tested, and manufactured in accordance with ASTM-F 1772 testing which meets PRCA/ANSI 1.0-1.3 and ANSI/ACCT 03-2016 standards in effect on the date of manufacture.

This Harness is not intended for Fall Arrest Applications.

WARNING! Never adjust the web tailing in the buckle to its absolute extended length, keep a 4 inch minimum requirement. Understand rock climbing, ice climbing, mountaineering and other related activities are extremely dangerous by their very nature. It is the sole responsibility of the buyer and the user of all climbing equipment to get the proper instruction and to practice caution when climbing or otherwise using this equipment.

Frequently inspect every piece of climbing equipment for possible damage or signs of wear. Climbing equipment cannot be expected to last forever, and it is up to the individual user to determine when to retire a piece of equipment.

CLIMB SMART! Seek qualified instruction, and take responsibility for yourself. Inspect this product regularly and retire it immediately if it shows signs of wear or damage. Do not attempt to use this product if you are not fully competent in its use and care. Treat this product as though your life depends on it. Improper care or use of this product can result in serious injury or death.



Figure 1



Figure 2

Clip into the Structural tie-ins only



Figure 3